

**LOCK LEGEND**

**(CYL)** Cylindrical Lock Preparation for use with various cylindrical locks conforming to ANSI/BHMA A156.115

**(M)** Mortise Lock Preparation for use with various mortise locks (with full escutcheon trim) conforming to ANSI/BHMA A156.115

**(MP)** Multi-Purpose Lock Preparation recommended for use with sectional trim mortise locks conforming to ANSI/BHMA A156.115. Preparation may be used for mortise exit hardware when thru-bolts are used for application. Installation of a lock edge filler plate provides a blank edge suitable for push & pull hardware or the application of various rim mounted locks or panic devices when thru-bolts are used for application

**(RMP)** Reinforced Multi-purpose Lock Preparation recommended for use with mortise exit hardware. Installation of a lock edge filler plate provides a blank edge suitable for push & pull hardware or the application of various rim mounted locks or panic devices.

**(BA)** Blank Active Lock Preparation recommended for use with various push & pull hardware or the application of various rim mounted locks or panic devices when thru-bolts are used for application.

**(RBA)** Reinforced Blank Active Lock Preparation recommended for use with various push & pull hardware or the application of various rim mounted locks or panic devices.

**(INA)** Inactive Door Preparation for use with various manual (and automatic) flush bolts conforming to ANSI/BHMA A156.115.

**(BI)** Blank Inactive Preparation recommended for use with various push & pull hardware or the application of various rim mounted locks or panic devices when thru-bolts are used for application. Not to be used as an active leaf.

**(RBI)** Reinforced Blank Inactive Preparation recommended for use with various push & pull hardware or the application of various rim mounted locks or panic devices. Not to be used as an active leaf.